

GX Series Irrigation Travelers



!WATER WHERE YOU NEED IT! ~WHEN YOU NEED IT!

The GX Series of travelers provide economical irrigation using an efficient, accurate and patented turbine drive system with a low-pressure requirement.

The simple drive system features an integral gearbox and turbine assembly directly driving the reel with accurate speed compensation and achieving the high speeds required for light application of water to delicate crops.



Standard Features

- Turbine driven with by-pass for irrigation or waste-water.
- Combined turbine and gearbox assembly with no belts or pulleys (except GX 540).
- 4-Speed gearbox for high speed and light applications of water (3 speed GX 540).
- PTO wind-in.
- Automatic speed compensation..
- Startec RainSpeed 060 digital tachometer.
- Adjustable width galvanized cart (adjustable height on GX 581 series and larger).
- Automatic cart lifting (manual on the GX 540 and GX 560)
- 15 foot heavy duty rubber supply hose with couplers.
- Galvanized chassis.
- Hydraulically operated stabilizer legs (mechanical on GX540, GX 560, GX 570)
- 360 degree rotation turntable.

1-770-459-4401 Inside Georgia

1-800-832-6224 Outside Georgia



- The **floating double axle** is available on the 690, 790 and 890 series to give additional stability and ease of transport in difficult terrain.
- **Fully galvanization** of the traveler for use in waste water applications where corrosive material is present (except for the GX 540).
- The **optional automatic shut off valve** will shut off the water to the machine at the end of the irrigation cycle. This can be used in conjunction with a pressure switch at the pump to shut off the water supply at the source.

- The **hydraulically operated turntable** makes rotation a simple and easy operation with fingertip controls.



- A **5 hp Honda engine** is optional in place of the turbine for the solids in animal waste disposal.

SERIES	MODEL	HOSE ID (INCH)	HOSE LENGTH (FT)	SPRINKLER	FLOW (GPM)	ACREAGE
540 GX	63/620	2.1	620	Komet 101	40-125	2.9-3.6
	63/985	2.1	985	Komet 101	40-125	4.0-5.3
560 GX	75/820	2.5	820	Komet 101	60-180	3.7-5.2
	82/525	2.7	525	Komet 101	80-210	3.0-4.0
570 GX	75/1150	2.5	1150	Komet 101	62-181	5.1-7.1
	82/985	2.7	985	Komet 101	80-210	4.4-6.9
	90/720	3.0	720	Komet 140	120-325	4.4-5.9
	90/985 EVO	3.0	985	Komet 140	120-325	6.0-9.0
581 GX	90/1050	3.0	1050	Komet 140	120-325	4.6-7.0
	90/1150	3.0	1150	Komet 140	120-325	6.1-9.0
	100/1150 EVO	3.3	1150	Komet 140	160-350	6.1-9.0
690 GX	110/720	3.7	720	Komet 160	220-450	6.0-7.4
	110/1210	3.7	1210	Komet 160	220-450	9.4-11.5
	120/885	4.0	885	Komet 202	250-575	7.1-8.9
790 GX	125/820	4.1	820	Komet 202	300-575	6.7-8.4
	110/1440	3.7	1440	Komet 160	220-450	11.0-12.5
890 GX	110/1476	3.7	1476	Komet 160	220-450	11.0-12.9
	125/1115	4.1	1115	Komet 202	300-575	8.8-10.8
	110/1640	3.7	1640	Komet 160	220-450	12.8-15.1
890 GX	125/1312	4.1	1312	Komet 202	300-575	8.5-10.8
	135/1250	4.5	1250	Komet 202	300-660	7.4-10.3

• Acreage based on irrigating 7 days a week, 15 hours a day and should be used as a guide only. For details refer to individual performance data.

Other hose sizes and lengths are available for special orders.....Please contact us for more details!



AgriBusiness International

70 Grady Knight Industrial Court
 Villa Rica, Georgia 30180 USA
 Phone: (770) 459-4401 Fax: (770) 459-6877
 Email: abirrigation@att.net

Dealer Label Here