

# JX Series Irrigation Travelers



In the field for over 40 years!

The JX series travelers provide the operator with simple set-up and operation with fingertip hydraulic controls. The standard hydraulics operate the jack, stabilizer legs, wheels and even the turntable, making large scale irrigation an easy low labor operation. As the wheels lift up – the machine is lowered gently onto the ground, giving additional stability and enabling the wheeled cart to load and lift automatically into the transport position at the end of the irrigation cycle.



## Standard Features

- Turbine driven with by-pass for irrigation or wastewater.
- 4 speed gearbox for variable applications rates of water.
- Automatic speed compensation.
- Digital speed read-out displays the pull-in speed at all times.
- Adjustable width and height galvanized cart.
- Hydraulically operated legs, wheels and jack with tractor connections.
- Galvanized chassis, stabilizer legs, frame and turntable (700, 800).
- Hydraulically lowering and raising of machine for additional stability.
- Heavy-Duty rubber supply hose with quick couplers.
- Komet slow-reverse sprinkler with 3 nozzles (optional Nelson sprinklers).
- 360 degree rotation hydraulic turntable.
- Combined turbine and gearbox assembly (no belts or pulleys).

# OPTIONS



- **Floating Double-axle** is available on the 700, 800 and 900 series (standard on the Major). It gives additional stability and ease of transport in difficult terrain.



- **Compressor** unit (standard on the Major), can be used to empty the hose of water at the end of each irrigation cycle.



- **Honda 6.5 hp Hydraulic Power Pack** is available to operate the machine hydraulics.



- **Automatic Shut-off Valve** will shut off the water at the machine at the end of the irrigation cycle. This can be used in conjunction with a pressure switch at the pump to turn off the water supply at the source.

- **Galvanization** of the complete machine.



**Rainmaster 2.6 Controller**

Series	Model	Hose I.D.	Hose Length	Sprinkler	Flow (gpm)	*Acreage
<b>700 JX</b>	110 / 1312	3.7"	1312'	Komet 160	420	98
	125 / 1115	4.1"	1115'	Komet 202	532	118
<b>800 JX</b>	110 / 1640	3.7"	1640'	Komet 160	330	75
	125 / 1312	4.1"	1312'	Komet 202	532	122
	135 / 1250	4.5"	1250'	Komet 202	660	122
<b>900 JX</b>	135 / 1640	4.5"	1640'	Komet 202	660	158
	140 / 1312	4.5"	1312'	Komet 202	650	151
	150 / 1250	5.0"	1250'	Komet 202	660	153
<b>MAJOR</b>	125 / 2200	4.1"	2200'	Komet 202	532	93
	140 / 1640	4.5"	1640'	Komet 202	650	140
<b>800 JXM</b>	135 / 1250	4.5"	1250'	Komet 202	660	153

• Acreage is based on irrigating 7 days a week, 15 hours a day and should be used as a guide only. For details refer to individual performance charts.

**Other hose sizes and lengths are available for special orders.....Please contact us for details!**



## AgriBusiness International

70 Grady Knight Industrial Court  
 Villa Rica, Georgia 30180 USA  
 Ph: (770) 459-4401  
 Fax: (770) 459-6877  
 Email: abiiirrigation@att.net

